



# Design Documents

*Release 2015.1.0 (cd5e6a5)*

**OPNFV**

March 23, 2016



<b>1</b>	<b>Report host fault to update server state immediately</b>	<b>3</b>
1.1	Problem description . . . . .	3
1.2	Proposed change . . . . .	4
1.3	Implementation . . . . .	6
1.4	Dependencies . . . . .	6
1.5	Testing . . . . .	6
1.6	Documentation Impact . . . . .	6
1.7	References . . . . .	6
<b>2</b>	<b>Notification Alarm Evaluator</b>	<b>7</b>
2.1	Problem description . . . . .	7
2.2	Proposed change . . . . .	7
2.3	Implementation . . . . .	10
2.4	Future lifecycle . . . . .	10
2.5	Dependencies . . . . .	10
2.6	Testing . . . . .	10
2.7	Documentation Impact . . . . .	10
2.8	References . . . . .	11
<b>3</b>	<b>Set maintenance period</b>	<b>13</b>
3.1	Problem description . . . . .	13
3.2	Proposed change . . . . .	13
3.3	Implementation . . . . .	16
3.4	Dependencies . . . . .	17
3.5	Testing . . . . .	17
3.6	Documentation Impact . . . . .	17
3.7	References . . . . .	17
3.8	History . . . . .	17



This is the directory to store design documents which may include draft versions of blueprints written before proposing to upstream OSS communities such as OpenStack, in order to keep the original blueprint as reviewed in OPNFV. That means there could be out-dated blueprints as result of further refinements in the upstream OSS community. Please refer to the link in each document to find the latest version of the blueprint and status of development in the relevant OSS community.

See also [https://wiki.opnfv.org/requirements\\_projects](https://wiki.opnfv.org/requirements_projects) .

---

**Note:** This is a specification draft of a blueprint proposed for OpenStack Nova Liberty. It was written by project member(s) and agreed within the project before submitting it upstream. No further changes to its content will be made here anymore; please follow it upstream:

- Current version upstream: <https://review.openstack.org/#/c/169836/>
- Development activity: <https://blueprints.launchpad.net/nova/+spec/mark-host-down>

**Original draft is as follow:**

---



## REPORT HOST FAULT TO UPDATE SERVER STATE IMMEDIATELY

<https://blueprints.launchpad.net/nova/+spec/update-server-state-immediately>

A new API is needed to report a host fault to change the state of the instances and compute node immediately. This allows usage of evacuate API without a delay. The new API provides the possibility for external monitoring system to detect any kind of host failure fast and reliably and inform OpenStack about it. Nova updates the compute node state and states of the instances. This way the states in the Nova DB will be in sync with the real state of the system.

### 1.1 Problem description

- Nova state change for failed or unreachable host is slow and does not reliably state compute node is down or not. This might cause same instance to run twice if action taken to evacuate instance to another host.
- Nova state for instances on failed compute node will not change, but remains active and running. This gives user a false information about instance state. Currently one would need to call “nova reset-state” for each instance to have them in error state.
- OpenStack user cannot make HA actions fast and reliably by trusting instance state and compute node state.
- As compute node state changes slowly one cannot evacuate instances.

#### 1.1.1 Use Cases

Use case in general is that in case there is a host fault one should change compute node state fast and reliably when using DB servicegroup backend. On top of this here is the use cases that are not covered currently to have instance states changed correctly: \* Management network connectivity lost between controller and compute node. \* Host HW failed.

Generic use case flow:

- The external monitoring system detects a host fault.
- The external monitoring system fences the host if not down already.
- The external system calls the new Nova API to force the failed compute node into down state as well as instances running on it.
- Nova updates the compute node state and state of the effected instances to Nova DB.

Currently nova-compute state will be changing “down”, but it takes a long time. Server state keeps as “vm\_state: active” and “power\_state: running”, which is not correct. By having external tool to detect host faults fast, fence host by powering down and then report host down to OpenStack, all these states would reflect to actual situation. Also if OpenStack will not implement automatic actions for fault correlation, external tool can do that. This could be configured for example in server instance METADATA easily and be read by external tool.

## 1.1.2 Project Priority

Liberty priorities have not yet been defined.

## 1.2 Proposed change

There needs to be a new API for Admin to state host is down. This API is used to mark compute node and instances running on it down to reflect the real situation.

Example on compute node is:

- When compute node is up and running: vm\_state: active and power\_state: running nova-compute state: up status: enabled
- When compute node goes down and new API is called to state host is down: vm\_state: stopped power\_state: shutdown nova-compute state: down status: enabled

vm\_state values: soft-delete, deleted, resized and error should not be touched. task\_state effect needs to be worked out if needs to be touched.

### 1.2.1 Alternatives

There is no attractive alternatives to detect all different host faults than to have a external tool to detect different host faults. For this kind of tool to exist there needs to be new API in Nova to report fault. Currently there must have been some kind of workarounds implemented as cannot trust or get the states from OpenStack fast enough.

### 1.2.2 Data model impact

None

### 1.2.3 REST API impact

- Update CLI to report host is down

nova host-update command

**usage:** nova host-update [--status <enable|disable>] [--maintenance <enable|disable>] [--report-host-down] <hostname>

Update host settings.

Positional arguments

<hostname> Name of host.

Optional arguments

--status <enable|disable> Either enable or disable a host.

--maintenance <enable|disable> Either put or resume host to/from maintenance.

--down Report host down to update instance and compute node state in db.

- Update Compute API to report host is down:

/v2.1/{tenant\_id}/os-hosts/{host\_name}

Normal response codes: 200 Request parameters



Parameter Style Type Description host\_name URI xsd:string The name of the host of interest to you.

```
{
  "host": { "status": "enable", "maintenance_mode": "enable" "host_down_reported": "true"
}
{
  "host": { "host": "65c5d5b7e3bd44308e67fc50f362aee6", "maintenance_mode": "enabled", "status":
    "enabled" "host_down_reported": "true"
}
}
```

- New method to nova.compute.api module HostAPI class to have a to mark host related instances and compute node down: set\_host\_down(context, host\_name)
- class novaclient.v2.hosts.HostManager(api) method update(host, values) Needs to handle reporting host down.
- Schema does not need changes as in db only service and server states are to be changed.

### 1.2.4 Security impact

API call needs admin privileges (in the default policy configuration).

### 1.2.5 Notifications impact

None

### 1.2.6 Other end user impact

None

### 1.2.7 Performance Impact

Only impact is that user can get information faster about instance and compute node state. This also gives possibility to evacuate faster. No impact that would slow down. Host down should be rare occurrence.

### 1.2.8 Other deployer impact

Developer can make use of any external tool to detect host fault and report it to OpenStack.

### 1.2.9 Developer impact

None

## 1.3 Implementation

### 1.3.1 Assignee(s)

Primary assignee: Tomi Juvonen Other contributors: Ryota Mibu

### 1.3.2 Work Items

- Test cases.
- API changes.
- Documentation.

## 1.4 Dependencies

None

## 1.5 Testing

Test cases that exists for enabling or putting host to maintenance should be altered or similar new cases made test new functionality.

## 1.6 Documentation Impact

New API needs to be documented:

- Compute API extensions documentation. <http://developer.openstack.org/api-ref-compute-v2.1.html>
- Nova commands documentation. [http://docs.openstack.org/user-guide-admin/content/novaclient\\_commands.html](http://docs.openstack.org/user-guide-admin/content/novaclient_commands.html)
- Compute command-line client documentation. [http://docs.openstack.org/cli-reference/content/novaclient\\_commands.html](http://docs.openstack.org/cli-reference/content/novaclient_commands.html)
- nova.compute.api documentation. <http://docs.openstack.org/developer/nova/api/nova.compute.api.html>
- High Availability guide might have page to tell external tool could provide ability to provide faster HA as able to update states by new API. <http://docs.openstack.org/high-availability-guide/content/index.html>

## 1.7 References

- OPNFV Doctor project: <https://wiki.opnfv.org/doctor>
- OpenStack Instance HA Proposal: <http://blog.russellbryant.net/2014/10/15/openstack-instance-ha-proposal/>
- The Different Facets of OpenStack HA: <http://blog.russellbryant.net/2015/03/10/the-different-facets-of-openstack-ha/>

## NOTIFICATION ALARM EVALUATOR

---

**Note:** This is spec draft of blueprint for OpenStack Ceilometer Liberty. To see current version: <https://review.openstack.org/172893> To track development activity: <https://blueprints.launchpad.net/ceilometer/+spec/notification-alarm-evaluator>

---

<https://blueprints.launchpad.net/ceilometer/+spec/notification-alarm-evaluator>

This blueprint proposes to add a new alarm evaluator for handling alarms on events passed from other OpenStack services, that provides event-driven alarm evaluation which makes new sequence in Ceilometer instead of the polling-based approach of the existing Alarm Evaluator, and realizes immediate alarm notification to end users.

### 2.1 Problem description

As an end user, I need to receive alarm notification immediately once Ceilometer captured an event which would make alarm fired, so that I can perform recovery actions promptly to shorten downtime of my service. The typical use case is that an end user set alarm on “compute.instance.update” in order to trigger recovery actions once the instance status has changed to ‘shutdown’ or ‘error’. It should be nice that an end user can receive notification within 1 second after fault observed as the same as other health- check mechanisms can do in some cases.

The existing Alarm Evaluator is periodically querying/polling the databases in order to check all alarms independently from other processes. This is good approach for evaluating an alarm on samples stored in a certain period. However, this is not efficient to evaluate an alarm on events which are emitted by other OpenStack servers once in a while.

The periodical evaluation leads delay on sending alarm notification to users. The default period of evaluation cycle is 60 seconds. It is recommended that an operator set longer interval than configured pipeline interval for underlying metrics, and also longer enough to evaluate all defined alarms in certain period while taking into account the number of resources, users and alarms.

### 2.2 Proposed change

The proposal is to add a new event-driven alarm evaluator which receives messages from Notification Agent and finds related Alarms, then evaluates each alarms;

- New alarm evaluator could receive event notification from Notification Agent by which adding a dedicated notifier as a publisher in pipeline.yaml (e.g. notifier://?topic=event\_eval).
- When new alarm evaluator received event notification, it queries alarm database by Project ID and Resource ID written in the event notification.
- Found alarms are evaluated by referring event notification.

- Depending on the result of evaluation, those alarms would be fired through Alarm Notifier as the same as existing Alarm Evaluator does.

This proposal also adds new alarm type “notification” and “notification\_rule”. This enables users to create alarms on events. The separation from other alarm types (such as “threshold” type) is intended to show different timing of evaluation and different format of condition, since the new evaluator will check each event notification once it received whereas “threshold” alarm can evaluate average of values in certain period calculated from multiple samples.

The new alarm evaluator handles Notification type alarms, so we have to change existing alarm evaluator to exclude “notification” type alarms from evaluation targets.

## 2.2.1 Alternatives

There was similar blueprint proposal “Alarm type based on notification”, but the approach is different. The old proposal was to adding new step (alarm evaluations) in Notification Agent every time it received event from other Open-Stack services, whereas this proposal intends to execute alarm evaluation in another component which can minimize impact to existing pipeline processing.

Another approach is enhancement of existing alarm evaluator by adding notification listener. However, there are two issues; 1) this approach could cause stall of periodical evaluations when it receives bulk of notifications, and 2) this could break the alarm portioning i.e. when alarm evaluator received notification, it might have to evaluate some alarms which are not assign to it.

## 2.2.2 Data model impact

Resource ID will be added to Alarm model as an optional attribute. This would help the new alarm evaluator to filter out non-related alarms while querying alarms, otherwise it have to evaluate all alarms in the project.

## 2.2.3 REST API impact

Alarm API will be extended as follows;

- Add “notification” type into alarm type list
- Add “resource\_id” to “alarm”
- Add “notification\_rule” to “alarm”

Sample data of Notification-type alarm:

```
{
  "alarm_actions": [
    "http://site:8000/alarm"
  ],
  "alarm_id": null,
  "description": "An alarm",
  "enabled": true,
  "insufficient_data_actions": [
    "http://site:8000/nodata"
  ],
  "name": "InstanceStatusAlarm",
  "notification_rule": {
    "event_type": "compute.instance.update",
    "query" : [
      {
        "field" : "traits.state",
```

```

        "type" : "string",
        "value" : "error",
        "op" : "eq",
    },
    ],
},
"ok_actions": [],
"project_id": "c96c887c216949acbd8b494863567",
"repeat_actions": false,
"resource_id": "153462d0-a9b8-4b5b-8175-9e4b05e9b856",
"severity": "moderate",
"state": "ok",
"state_timestamp": "2015-04-03T17:49:38.406845",
"timestamp": "2015-04-03T17:49:38.406839",
"type": "notification",
"user_id": "c96c887c216949acbd8b494863567"
}

```

“resource\_id” will be referred to query alarm and will not be check permission and belonging of project.

## 2.2.4 Security impact

None

## 2.2.5 Pipeline impact

None

## 2.2.6 Other end user impact

None

## 2.2.7 Performance/Scalability Impacts

When Ceilometer received a number of events from other OpenStack services in short period, this alarm evaluator can keep working since events are queued in a messaging queue system, but it can cause delay of alarm notification to users and increase the number of read and write access to alarm database.

“resource\_id” can be optional, but restricting it to mandatory could be reduce performance impact. If user create “notification” alarm without “resource\_id”, those alarms will be evaluated every time event occurred in the project. That may lead new evaluator heavy.

## 2.2.8 Other deployer impact

New service process have to be run.

## 2.2.9 Developer impact

Developers should be aware that events could be notified to end users and avoid passing raw infra information to end users, while defining events and traits.

## 2.3 Implementation

### 2.3.1 Assignee(s)

**Primary assignee:** r-mibu

**Other contributors:** None

**Ongoing maintainer:** None

### 2.3.2 Work Items

- New event-driven alarm evaluator
- Add new alarm type “notification” as well as AlarmNotificationRule
- Add “resource\_id” to Alarm model
- Modify existing alarm evaluator to filter out “notification” alarms
- Add new config parameter for alarm request check whether accepting alarms without specifying “resource\_id” or not

## 2.4 Future lifecycle

This proposal is key feature to provide information of cloud resources to end users in real-time that enables efficient integration with user-side manager or Orchestrator, whereas currently those information are considered to be consumed by admin side tool or service. Based on this change, we will seek orchestrating scenarios including fault recovery and add useful event definition as well as additional traits.

## 2.5 Dependencies

None

## 2.6 Testing

New unit/scenario tests are required for this change.

## 2.7 Documentation Impact

- Proposed evaluator will be described in the developer document.
- New alarm type and how to use will be explained in user guide.

## 2.8 References

- OPNFV Doctor project: <https://wiki.opnfv.org/doctor>
- Blueprint “Alarm type based on notification”: <https://blueprints.launchpad.net/ceilometer/+spec/alarm-on-notification>





## SET MAINTENANCE PERIOD

<https://blueprints.launchpad.net/nova/+spec/set-maintenance-period>

When compute host going for maintenance it has to be possible to set the wanted maintenance start and end time.

### 3.1 Problem description

Admin needs to be able to set wanted maintenance period, so server owner can also prepare for maintenance. Server owner might want to have different actions for his server depending when and how long the maintenance takes. This is very important for services that needs to run without any downtime because of the maintenance.

#### 3.1.1 Use Cases

As admin I want to set maintenance period for certain host.

As owner of a server I want to prepare for maintenance to minimize downtime and keep capacity on needed level.

As owner of a server I want to have different actions for different servers depending application on server, when and how long the maintenance will last. To achieve this, there needs to be information about when maintenance is going to happen. Actions for servers are not in scope of this spec. It might be future work to define some auto recovery or some other configured actions, but currently that is just left outside of Nova scope. This can be complex and it might be server is moved, removed or even left to host when maintenance is to take place.

### 3.2 Proposed change

New admin API endpoint `PUT /v2.1/{tenant_id}/os-services/maintenance` should be added having `host`, `binary`, `maintenance_start` and `maintenance_end` parameters in request. API will tell when actual maintenance for host will happen and it is also used to unset maintenance period. As in `disable nova-compute` case only the scheduling will be stopped, this new API will tell the time period when actually host maintenance is performed and servers can also therefore be down.

If no `maintenance_end` defined while `maintenance_start` defined, it means the host will be removed. Calling API with empty timestamps in `maintenance_start` and `maintenance_end` will indicate there is no ongoing maintenance and this is also the default value in Nova service DB for these new fields. Service enable/disable is expected to be called separately before and after maintenance.

`service.update` notification should have new version to include `maintenance_start` and `maintenance_end` information. Calling of new maintenance API should also trigger this notification.

Alarm should be risen for server owners telling list of their servers that are on a host that is going for maintenance. Also the `maintenance_start` and `maintenance_end` should be visible in the alarm. Host should not be exposed to

owner, so alarm should not contain that information. There should also be alarm when maintenance over and it needs to contain information to map it to start maintenance alarm. tbd better in the notification section.

Maintenance should also be shown to server owner by adding `OS-EXT-SRV-ATTR:maintenance_start` and `OS-EXT-SRV-ATTR:maintenance_end` parameters to the `/servers/{server_id}` and `/servers/detail` endpoints. New policy should be added to control visibility of the new parameters:

“os\_compute\_api:servers:show:maintenance”: “rule:admin\_or\_owner”

Currently only ability to show nova-compute service disabled as `MAINTENANCE` in `host_status` parameter, but policy for this defaults to admin. In NFV it will be configured also to owner.

### 3.2.1 Alternatives

tbd

### 3.2.2 Data model impact

Nova Service DB will have new fields `maintenance_start` and `maintenance_end`.

### 3.2.3 REST API impact

New API microversion is needed to add new API: `PUT /v2.1/{tenant_id}/os-services/maintenance` Same time also visibility to response of `GET /v2.1/{tenant_id}/servers/{server_id}` and `GET /v2.1/{tenant_id}/servers/detail` with new parameters `OS-EXT-SRV-ATTR:maintenance_start` and `OS-EXT-SRV-ATTR:maintenance_end`. Parameters visibility controlled by new policy.

Example of setting 2 hours maintenance period:

```
PUT /v2.1/{tenant_id}/os-services/maintenance
{
  "host": "compute1",
  "binary": "nova-compute",
  "maintenance_start": "2016-03-22T01:00:00",
  "maintenance_end": "2016-03-22T03:00:00"
}

200 OK
{
  "service": {
    "binary": "nova-compute",
    "host": "compute1",
    "maintenance_start": "2016-03-22T01:00:00.000000",
    "maintenance_end": "2016-03-22T03:00:00.000000"
  }
}
```

Example to unset maintenance:

```
PUT /v2.1/{tenant_id}/os-services/maintenance
{
  "host": "compute1",
  "binary": "nova-compute",
  "maintenance_start": "",
  "maintenance_end": ""
}
```

```

}
200 OK
{
  "service": {
    "binary": "nova-compute",
    "host": "compute1",
    "maintenance_start": "",
    "maintenance_end": ""
  }
}

```

Example of indicating host removal:

```

PUT /v2.1/{tenant_id}/os-services/maintenance
{
  "host": "compute1",
  "binary": "nova-compute",
  "maintenance_start": "2016-03-22T01:00:00",
  "maintenance_end": ""
}
200 OK
{
  "service": {
    "binary": "nova-compute",
    "host": "compute1",
    "maintenance_start": "2016-03-22T01:00:00.000000",
    "maintenance_end": ""
  }
}

```

Setting timestamps in the past will be considered as an error and `maintenance_end` has to be after `maintenance_start` or empty:

```
400 Bad Request
```

### 3.2.4 Security impact

None

### 3.2.5 Notifications impact

New version of `service.update` notification needs to have new parameters `maintenance_start` and `maintenance_end` and notification needs to be triggered if new maintenance API is called:

```

{
  "priority": "INFO",
  "event_type": "service.update",
  "timestamp": "2016-03-22 00:46:25.211575",
  "publisher_id": "nova-compute:controller",
  "payload": {
    "nova_object.version": "1.0",
    "nova_object.name": "ServiceStatusPayload",
    "nova_object.namespace": "nova",
    "nova_object.data": {

```

```
    "binary": "nova-compute",
    "report_count": 1,
    "topic": "compute",
    "host": "controller",
    "version": 3,
    "disabled": true,
    "forced_down": false,
    "last_seen_up": "2016-03-22T00:46:25Z",
    "disabled_reason": "Going to maintenance",
    "maintenance_start": "2016-03-22T01:00:00Z",
    "maintenance_end": "2016-03-22T03:00:00Z",
  },
  "message_id": "8516b5c7-c6a7-43a4-9ad1-df447f318afb"
}
```

tbd, maintenance alarm.

### 3.2.6 Other end user impact

None

### 3.2.7 Performance Impact

None

### 3.2.8 Other deployer impact

None

### 3.2.9 Developer impact

None

## 3.3 Implementation

### 3.3.1 Assignee(s)

**Primary assignee:** tomi-juvonen-q

### 3.3.2 Work Items

Nova service DB changes. New maintenance API. Notification. Alarm.

## 3.4 Dependencies

Continues work started in Mitaka:

<https://blueprints.launchpad.net/nova/+spec/get-valid-server-state>

## 3.5 Testing

Unit and functional tests will be added.

## 3.6 Documentation Impact

API changes need to be documented for new microversion. Maintenance documentation should be updated.

## 3.7 References

Requirements of OPNFV Doctor project: <http://artifacts.opnfv.org/doctor/docs/requirements/requirements.pdf>

## 3.8 History

Table 3.1: Revisions

Release Name	Description
Newton	Introduced